

Fire Proof Storage

30 minutes according to EN 14470-1



- Fire rated 30 minutes.
- Fire tested according to EN 14470-1.
- Approved according to FM standard 6050
- 100 mm ventilation openings.
- Self-closing doors that can be set up and close automatically when the temperature rises to 500C.
- Swing doors with three-point lock and cylinder lock.



F30KEM1



F30KEM2



F30KEM3



F30KEM4



F30KEM5



F30KEM4G



F30KEM5G

Model	External size (mm)	Internal size (mm)	Tray	Tray size	Shelves	Ventilation	Glass doors
USF30KEM1	H635xB605xD550	H366xB491xD419	1 pc	20 l	0	100 mm back	No
USF30KEM2	H635xB1115xD550	H366xB1001xD419	1 pc	41 l	0	100 mm back	No
USF30KEM3	H1198xB1092xD537	H799xB978xD325	1 pc	31 l	1	100 mm ceiling	No
USF30KEM4	H11980xB1092xD537	H1581xB491xD419	1 pc	20 l	3	100 mm ceiling	No
USF30KEM4G	H11980xB1092xD537	H1581xB491xD419	1 pc	20 l	3	100 mm ceiling	Yes
USF30KEM5	H1980xB1115xD550	H1581xB1001xD419	1 pc	41 l	3	100 mm ceiling	No
USF30KEM5G	H1980xB1115xD550	H1581xB1001xD419	1 pc	41 l	3	100 mm ceiling	Yes

THIS DOCUMENT CONTAINS GENERAL PRODUCT INFORMATION THAT IS REVISIONALLY REVISED AND CHANGED

UniSkill MediTech AB
MADE IN SWEDEN

info@uniskill.se
www.uniskill.se

TPI1030-00

